


NAC2403-H2.3



The Noliac shear stack NAC2403-H2.3 features shear motion on the X-axis. NAC2403-H2.3 measures 10x10 mm with a height of 2.3 mm and provides a free stroke of 3 μ m and a capacitance of 6.6 nF.

SPECIFICATIONS

Attributes	Value	Tolerance
Chamfers	X 0,00	
Length / outer diameter	10 mm	+/-0.20 mm
Width / inner diameter	10 mm	+/-0.20 mm
Height	2.3 mm	+/-0.05 mm
Operating voltage, max.	\pm 320 V	
Free stroke, from -Vmax to +Vmax	3 μ m	+/- 20%
Capacitance	6.6 nF	+/- 20%
Maximum operating temperature	150 °C	
Material	NCE51	
Unloaded resonance frequency	350 kHz	


DRAWINGS

Multi-axis piezoelectric shear actuator stacks

Standard features

- X and X/Y motions
- Smart design
- -320 V to +320 V maximum operating voltage for all motions
- Ideal for all stick and slip and nanopositioning applications
- Top and bottom isolations included
- Non-magnetic ultra-thin electrodes

The informative here opposite drawing is for a 2 shear plate configuration of X-motion. See the table below for other standard offers.



WIRES

As standard, the shear stacks are delivered with these wires:

- 28 AWG PTFE Insulated Wires (red for X-motion and blue or yellow for Y-motion).



Your piezo partner

Please contact us for other wiring options.